THERMOMETERS

DIGIVET, DIGIFLASH, DIGIFIX, DIGIFARM



injection | surgery | orthopedics | **hospitalisation** | capture | protection | hygiene | livestock

génia

DIGIVET

NEW DESIGN

FLEXIBLE TIP



Digital thermometer for small animals.

- **Flexible** tip, length **5,6 cm**.
- Temperature measurement in **10 seconds**.
  - Recording the last value.
  - Temperature range: 32 à 49.9 °C / 90 à 109,9 °F.
  - Accuracy: 0,1 °C / 0,2 °F.
  - Alarm indicating the end of measurement.
- Low battery symbol display.
- Auto power-off.
- Tightness: **IP54**.
- Shock resistant.

Supplied in a transparent polycarbonate box.

Code	Length	Tip length
227970	12,8 cm	5,6 cm

Outer packaging: master case of 12 or 240

DIGIFLASH

FLEXIBLE TIP



Digital thermometer for small and large animals.

- **Flexible** tip, length **7 cm**.
- Temperature measurement in **10 seconds**.
  - Recording the last value.
  - Temperature range: 32 à 43 °C / 90 à 110 °F.
  - Accuracy: 0,01 °C / 0,02 °F.
  - Alarm indicating the end of measurement.
- Low battery symbol display.
- Auto power-off.
- Tightness: **IP56**.
- Shock resistant.

Supplied in a transparent polycarbonate box.

Code	Length	Tip length
227972	15,5 cm	7 cm

Outer packaging: master case of 12 or 240

DIGIFIX

RIGID TIP



Digital thermometer for small and large animals.

- Single-piece slim **rigid** tip, length **7,5 cm**.
- Temperature measurement in **10 seconds**.
  - Recording the last 5 values.
  - Temperature range: 32 à 43 °C / 90 à 110 °F.
  - Accuracy : 0,1 °C / 0,2 °F.
  - Alarm indicating the end of measurement.
- Low battery symbol display.
- Auto power-off.
- Tightness: **IP56**.
- Shock resistant.

Supplied in a transparent polycarbonate box.

Code	Length	Tip length
227978	15,5 cm	7,5 cm

Outer packaging: master case of 12 or 240

DIGIFARM

RIGID TIP



Digital thermometer for large animals.

- Single-piece slim **rigid** tip, length **15,3 cm**.
- Temperature measurement in **10 seconds**.
  - Recording the last value.
  - Temperature range: 32,00 à 42,99°C / 89,60 à 109,38 °F.
  - Accuracy: 0,1°C / 0,20°F.
  - Alarm indicating the end of measurement.
- Low battery symbol display.
- Auto power-off.
- Tightness: **IP56**.
- Shock resistant.

Supplied in a transparent polycarbonate box.
Battery included.

Code	Length	Tip length
227982	23 cm	15,3 cm

Outer packaging: master case of 12 or 240